

RAPIDfire Nozzle



- ◆ Pressure remains constant at desire flow
- ◆ Durable light hard anodized construction
- ◆ Straight stream to wide fog and flush without shut-off
- ◆ Molded rubber bumper with flexible fog teeth creates thick fog pattern
- ◆ Pistol grip handle designed for greater comfort and control to fire
- ◆ 1/5"/2.5" male instantaneous / Storz / BSP or NH or NST threaded inlets available

Specification

Item Code # **NFF-NZ-RFN**

Type	Constant Pressure							
Model	RAPIDfire (RF)							
Series	Inlet		Style		Flow Range		Fog Teeth	
RF	A	1" NST (F)	1	One Piece Nozzle with Control Valve	5K	60-180 GPM @ 55 PSI (3.8 Bar)	SP	SPINNING POLYIMIDE
	B	1.5" NST (F)			5L	95-225 GPM @ 55 PSI (3.8 Bar)	SM	SPINNING STAINLESS STEEL
	C	2.5" NST (F)	2	One Piece Nozzle with Control Valve and Pistol Grip	5K	10-100 GPM @ 75 PSI (5 Bar)	MR	MOULDED RUBBER
	D	1" BSP (F)			5L	60-200 GPM @ 75 PSI (5 Bar)		
	E	1.5" BSP (F)	3	Two Piece Nozzle with Tip and Control Valve	5M	90-250 GPM @ 75 PSI (5 Bar)		
	F	2.5" BS INST (M)			7K	10-125 GPM @ 100 PSI (7 Bar)		
	G	1" STORZ	4	Two Piece Nozzle with Tip and Control Valve and Pistol Grip	7L	60-200 GPM @ 100 PSI (7 Bar)		
	H	1.5" STORZ			7M	90-250 GPM @ 100 PSI (7 Bar)		
	I	2.5" STORZ						

www.newage-india.in

NEWAGE[®]
FIRE FIGHTING CO. LTD.

Address : "NKB House", P. O. Box No.: 14, Mehta Market, Surendranagar - 363 001, Gujarat, India
Phone No. : +91 2752 288 000, +91 99250 63730 | Fax : +91 11 66173355 | Email : info@newage-india.in