

SUPERfire Nozzle



- ◆ Special design gives low back pressure
- ◆ Constant Selectable gallonage Nozzle with multiple flow setting
- ◆ Durable light hard anodized construction
- ◆ Straight stream to dense fog & flush without shut off
- ◆ Ball valve for flow control
- ◆ Anti-Slip polymide moulded pistol grip
- ◆ Female inlet with instantaneous male Coupling, NH or NPSH threads
- ◆ NFPA 1964 compliant

Specification

Item Code # **NFF-NZ-SFN**

Type	Selectable Gallonage							
Model	SUPERfire (SF)							
Series	Inlet		Style	Flow Range		Fog Teeth		
SF	A	1" NST (F)	1	One Piece Nozzle with Control Valve	5K	13-25-40-60 GPM @ 75 PSI (5 Bar)	SP	SPINNING POLYIMIDE
	B	1.5" NST (F)			5L	30-60-95-125 GPM @ 75 PSI (5 Bar)	SM	SPINNING STAINLESS STEEL
	C	2.5" NST (F)	2	One Piece Nozzle with Control Valve and Pistol Grip	5M	30-60-95-125-150-200 GPM @ 75 PSI (5 Bar)	MR	MOULDED RUBBER
	D	1" BSP (F)			5N	95-125-150-200-250 GPM @ 75 PSI (5 Bar)		
	E	1.5" BSP (F)	3	Two Piece Nozzle with Tip and Control Valve	7K	13-25-40-60 GPM @ 100 PSI (7 Bar)		
	F	2.5" BS INST (M)			7L	30-60-95-125 GPM @ 100 PSI (7 Bar)		
	G	1" STORZ	4	Two Piece Nozzle with Tip and Control Valve and Pistol Grip	7M	30-60-95-125-150-200 GPM @ 100 PSI (7 Bar)		
	H	1.5" STORZ			7N	95-125-150-200-250 GPM @ 100 PSI (7 Bar)		
	I	2.5" STORZ						

www.newage-india.in

NEWAGE[®]
FIRE FIGHTING CO. LTD.

Address : "NKB House", P. O. Box No.: 14, Mehta Market, Surendranagar - 363 001, Gujarat, India
Phone No. : +91 2752 288 000, +91 99250 63730 | Fax : +91 11 66173355 | Email : info@newage-india.in